



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: 20151 PM XERAMIC Instant Gasket Black**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture**
One component temperature resistant silicone sealing for high temperature application
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Petromark Automotive Chemicals
Rooswijkweg 316, 1951 ME Velsen-Noord, The Netherlands
www.petromark.eu • info@petromark.eu
Tel. +31 (0)251 211397
- **Further information obtainable from:**
Petromark Automotive Chemicals: info@petromark.eu
- **1.4 Emergency telephone number:**
Petromark Automotive Chemicals: Tel. +31 (0)251 211397

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
The product is tested according 92/69/EC and is not classified as irritating to skin and eyes.
Aerosol 3 H229 Pressurised container: May burst if heated.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms** Void
- **Signal word** Warning
- **Hazard statements**
H229 Pressurised container: May burst if heated.
- **Precautionary statements**
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 2)

GB



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

Trade name: 20151 PM XERAMIC Instant Gasket Black

· vPvB: Not applicable.

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 811-97-2 EINECS: 212-377-0 Reg.nr.: 01-2119459374-33-xxxx	1,1,1,2-tetrafluoroethane substance with a Community workplace exposure limit	1 - 2.5%
CAS: 4253-34-3 EINECS: 224-221-9 Reg.nr.: 01-2119962266-32-xxxx	methylsilanetriyl triacetate ⚠ Skin Corr. 1B, H314; ⚠ Acute Tox. 4, H302	1 - 2.5%
CAS: 17865-07-5 EINECS: 241-816-9 Reg.nr.: 01-2119966899-07-xxxx	Propyltriacetoxysilan ⚠ Skin Corr. 1B, H314	1 - 2.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:** If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. Remove contact lenses, if present and easy to do. Continue rinsing. Then consult a doctor.

· After swallowing:

Seek medical treatment.

Rinse out mouth and then drink plenty of water if person is conscious.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray.· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· 5.2 Special hazards arising from the substance or mixture

Nitrogen oxides (NO_x)

In case of fire, the following can be released:

Carbon monoxide (CO)

Danger of bursting by heating.

· 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained respiratory protective device.

(Contd. on page 3)



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

Trade name: 20151 PM XERAMIC Instant Gasket Black

(Contd. of page 2)

· Additional information

- Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
- Cool endangered receptacles with water spray and remove it out of emergency area if possible.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures** Not required.
- 6.2 Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
- 6.3 Methods and material for containment and cleaning up:**
 - Pick up mechanically.
 - Dispose of the material collected according to regulations.
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
- 6.4 Reference to other sections**
 - No dangerous substances are released.
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.
- Information about fire - and explosion protection:**
 - Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- 7.2 Conditions for safe storage, including any incompatibilities**
- Storage:**
- Requirements to be met by storerooms and receptacles:**
 - Store only in the original receptacle.
 - Store in a cool location under dry conditions in well sealed receptacles
 - Observe official regulations on storing packagings with pressurised containers.
 - Do not store in gangways or stairways.
- Information about storage in one common storage facility:**
 - Do not store together with oxidizing and selfigniting materials.
- Further information about storage conditions:**
 - Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
 - Do not store together with oxidizing and self-igniting material.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

Trade name:20151 PM XERAMIC Instant Gasket Black

(Contd. of page 3)

· 8.1 Control parameters**· Ingredients with limit values that require monitoring at the workplace:****811-97-2 1,1,1,2-tetrafluoroethane**WEL (Great Britain) Long-term value: 4240 mg/m³, 1000 ppm**· DNELs****811-97-2 1,1,1,2-tetrafluoroethane**

Inhalative	wrks, long, system	13936 mg/m ³ (mouse)
	cstm, long, system	2476 mg/m ³ (mouse)

4253-34-3 methylsilanetriyl triacetate

Oral	cstm, long, system, oral	1 mg/kg/d (mouse)
	cstm, short, system	1 mg/kg bw/d (rabbit)
Dermal	wrks, long, system	14.5 mg/kg/d (mouse)
	cstm, long, system	7.2 mg/kg/d (mouse)
	wrks, short, system	14.5 mg/kg bw/d (rabbit)
Inhalative	cstm, short, system	7.2 mg/kg bw/d (rabbit)
	wrks, long, system	25 mg/m ³ (mouse)
	cstm, long, system	6.3 mg/m ³ (mouse)
	wrks, short, system	25 mg/m ³ (rabbit)
	wrks, long, local	31 mg/m ³ (rabbit)
	cstm, long, local	5.1 mg/m ³ (mouse)
	cstm, short, local	5.1 mg/m ³ (rabbit)
	cstm, short, system	6.3 mg/m ³ (rabbit)
wrks, short, local	31 mg/m ³ (mouse)	

17865-07-5 Propyltriacetoxysilan

Oral	cstm, long, system, oral	6.05 mg/kg/d (mouse)
Dermal	wrks, long, system	12.11 mg/kg/d (mouse)
	cstm, long, system	6.05 mg/kg/d (rabbit)
Inhalative	wrks, long, system	85.39 mg/m ³ (mouse)
	cstm, long, system	21.06 mg/m ³ (rabbit)

· PNECs**811-97-2 1,1,1,2-tetrafluoroethane**

Oral	fresh water	0.1 mg/l (daphnia)
	sediment (fresh water)	0.75 mg/(kg dw) (daphnia)
	STP	73 mg/l (daphnia)
	marine water	0.01 mg/l (daphnia)
	intermittent release	1.0 mg/l (daphnia)

4253-34-3 methylsilanetriyl triacetate

Oral	fresh water	1 mg/l (daphnia)
	sediment (fresh water)	3.4 mg/(kg dw) (daphnia)
	STP	10 mg/l (daphnia)

(Contd. on page 5)



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

Trade name: 20151 PM XERAMIC Instant Gasket Black

(Contd. of page 4)

	soil	0.145 mg/(kg dw) (daphnia)
	sediment (marine water)	0.34 mg/(kg bw) (daphnia)
	marine water	0.1 mg/l (daphnia)
	intermittent release	10 mg/l (daphnia)
17865-07-5 Propyltriacetoxysilan		
Oral	fresh water	0.02441 mg/l (daphnia)
	sediment (fresh water)	0.01457 mg/(kg dw) (daphnia)
	STP	10.55 mg/l (daphnia)
	soil	0.00336 mg/(kg dw) (daphnia)
	sediment (marine water)	0.001457 mg/(kg bw) (daphnia)
	marine water	0.002441 mg/l (daphnia)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Do not eat, drink, smoke or sniff while working.

Wash hands before breaks and at the end of work.

· **Respiratory protection:**

Not necessary if room is well-ventilated.

Short term filter device:

Filter A/P2

· **Protection of hands:**

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

· **Material of gloves**

Recommended thickness of the material: ≥ 0.5 mm

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Goggles recommended during refilling

· **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: paste-like

(Contd. on page 6)



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

Trade name: 20151 PM XERAMIC Instant Gasket Black

(Contd. of page 5)

Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	3.0 %
Upper:	16 %
· Vapour pressure:	Not applicable.
· Density at 20 °C:	1.02 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Organic solvents:	0.0 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Danger of bursting.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No decomposition if used according to specifications.

GB

(Contd. on page 7)



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

Trade name: 20151 PM XERAMIC Instant Gasket Black

(Contd. of page 6)

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **LD/LC50 values relevant for classification:**

4253-34-3 methylsilanetriyl triacetate		
Oral	LD50	1600 mg/kg (rat)
- **Primary irritant effect:**
- **Skin corrosion/irritation**
No irritant effect.
test system/specie: rabbit
- **Serious eye damage/irritation**
No irritant effect.
test system/specie: rabbit
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity** No further relevant informations available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
----------	---

(Contd. on page 8)

GB



Safety data sheet
according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016



Trade name: 20151 PM XERAMIC Instant Gasket Black

(Contd. of page 7)

08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 10	waste adhesives and sealants other than those mentioned in 08 04 09
16 00 00	WASTES NOT OTHERWISE SPECIFIED IN THE LIST
16 05 00	gases in pressure containers and discarded chemicals
16 05 04*	gases in pressure containers (including halons) containing hazardous substances
15 00 00	WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED
15 01 00	packaging (including separately collected municipal packaging waste)
15 01 04	metallic packaging

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number · ADR, IMDG, IATA	UN1950
· 14.2 UN proper shipping name · ADR · IMDG · IATA	1950 AEROSOLS AEROSOLS AEROSOLS, non-flammable
· 14.3 Transport hazard class(es) · ADR 	2 5A Gases. 2.2
· IMDG, IATA 	2.2 2.2
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Code	Warning: Gases. - F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above

(Contd. on page 9)



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

Trade name: 20151 PM XERAMIC Instant Gasket Black

(Contd. of page 8)

· Segregation Code	1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	3
· Tunnel restriction code	E (Dangerous goods in "LQ" with more than 8 tons gross mass of LQ falls under the tunnel restriction code "E")
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.2

*

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 20
- **National regulations:**
- **Waterhazard class:** Water hazard class 1 (Self-assessment): slightly hazardous for water.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
- **Abbreviations and acronyms:**
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

(Contd. on page 10)

GB



Safety data sheet according to 1907/2006/EC, Annex II

Printing date 08.06.2016

Version number 1

Revision: 09.03.2016

Trade name:20151 PM XERAMIC Instant Gasket Black

(Contd. of page 9)

ICAO: International Civil Aviation Organisation

ctsm, long, system: general population, long-term exposure, systematic effects

cstm, short, system: general population, acute / short-term exposure, systematic effects

wrks, long, system: workers, long-term exposure - systemic effects

wrks, short, system: workers, acute / short-term exposure - systemic effects

cstm, long, local: general population, long-term exposure, local effects

STP: sewage treatment plant

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Aerosol 3: Aerosols – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

· *** Data compared to the previous version altered.**

GB