

## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: **20311 PM Xeramic® Carb & Choke Cleaner**

Article number: 20311

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

Product category PC35 Washing and cleaning products (including solvent based products)

##### Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Cleaner solvent

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

Petromark Automotive Chemicals

Rooswijkweg 316, 1951 ME Velsen-Noord, The Netherlands

www.petromark.eu info@petromark.eu Tel. +31 (0)251 211397

##### Further information obtainable from:

Petromark Automotive Chemicals: info@petromark.eu

#### 1.4 Emergency telephone number:

Petromark Automotive Chemicals, Tel. +31 (0)251 211397

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

## Safety data sheet

### According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 1)

**· Hazard pictograms**


GHS02 GHS07 GHS08

**· Signal word** Danger

**· Hazard-determining components of labelling:**

 toluene  
 butanone / MEK

**· Hazard statements**

 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H361d Suspected of damaging the unborn child.  
 H336 May cause drowsiness or dizziness.  
 H373 May cause damage to organs through prolonged or repeated exposure.

**· Precautionary statements**

 P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P251 Do not pierce or burn, even after use.  
 P260 Do not breathe spray.  
 P211 Do not spray on an open flame or other ignition source.  
 P280 Wear protective gloves / eye protection.  
 P273 Avoid release to the environment.  
 P271 Use only outdoors or in a well-ventilated area.  
 P301+P310 IF SWALLOWED: Immediately call a doctor.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P331 Do NOT induce vomiting.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P403 Store in a well-ventilated place.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Additional information:**

Buildup of explosive mixtures possible without sufficient ventilation.

**· 2.3 Other hazards**
**· Results of PBT and vPvB assessment**
**· PBT:** Not applicable.

**· vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

**· 3.2 Mixtures**
**· Description:** Active substance with propellant

**· Dangerous components:**

CAS: 108-88-3	toluene	25-<50%
EINECS: 203-625-9	Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	
Reg.nr.: 01-2119471310-51		

(Contd. on page 3)



## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 2)

CAS: 78-93-3 EINECS: 201-159-0 Reg.nr.: 01-2119457290-43	butanone / MEK Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25	propan-2-ol Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	10-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas C, H280	10-<25%
CAS: 111-76-2 EINECS: 203-905-0 Reg.nr.: 01-2119475108-36	2-butoxyethanol Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319	0.1-<1.0%

**Ingredients according to detergents guideline 648/2004/EC**

aromatic hydrocarbons, aliphatic hydrocarbons

≥ 30%

**Additional information:****SECTION 4: First aid measures**

- **4.1 Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**  
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

**SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**  
Water haze  
Fire-extinguishing powder  
Carbon dioxide  
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

**SECTION 6: Accidental release measures**

- **6.1 Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents

(Contd. on page 4)



## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 3)

- **6.4 Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**  
Do not spray onto a naked flame or any incandescent material.  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**  
Store in a cool location.  
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**  
Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**  
Keep receptacle tightly sealed.  
Do not seal receptacle gas tight.  
Store in cool, dry conditions in well sealed receptacles.  
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

### SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

**Ingredients with limit values that require monitoring at the workplace:****108-88-3 toluene**

WEL	Short-term value: 384 mg/m <sup>3</sup> , 100 ppm
	Long-term value: 191 mg/m <sup>3</sup> , 50 ppm
Sk	

**78-93-3 butanone / MEK**

WEL	Short-term value: 899 mg/m <sup>3</sup> , 300 ppm
	Long-term value: 600 mg/m <sup>3</sup> , 200 ppm
Sk, BMGV	

**67-63-0 propan-2-ol**

WEL	Short-term value: 1250 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 999 mg/m <sup>3</sup> , 400 ppm

**74-98-6 propane**

OEL	Short-term value: 3600 mg/m <sup>3</sup> , 2000 ppm
	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm

(Contd. on page 5)

GB



## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 4)

**111-76-2 2-butoxyethanol**

WEL	Short-term value: 246 mg/m <sup>3</sup> , 50 ppm Long-term value: 123 mg/m <sup>3</sup> , 25 ppm Sk, BMGV
-----	---

· **DNELs****108-88-3 toluene**

Oral	DNEL Long term-systemic	8.13 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	226 mg/kg bw/day (Consumer) 384 mg/kg bw/day (Worker)
Inhalative	DNEL Acute-systemic	226 mg/m <sup>3</sup> (Consumer) 384 mg/m <sup>3</sup> (Worker)
	DNEL Acute-local	226 mg/m <sup>3</sup> (Consumer) 384 mg/m <sup>3</sup> (Worker)
	DNEL Long term-systemic	56.5 mg/m <sup>3</sup> (Consumer) 192 mg/m <sup>3</sup> (Worker)
	DNEL Long term-local	192 mg/m <sup>3</sup> (Worker)

**78-93-3 butanone / MEK**

Oral	DNEL Long term-systemic	31 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	412 mg/kg bw/day (Consumer) 1161 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	106 mg/m <sup>3</sup> (Consumer) 600 mg/m <sup>3</sup> (Worker)

**67-63-0 propan-2-ol**

Oral	DNEL Long term-systemic	26 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	319 mg/kg bw/day (Consumer) 888 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	89 mg/m <sup>3</sup> (Consumer) 500 mg/m <sup>3</sup> (Worker)

· **Ingredients with biological limit values:****78-93-3 butanone / MEK**

BMGV	70 µmol/L Medium: urine Sampling time: post shift Parameter: butan-2-one
------	---

**111-76-2 2-butoxyethanol**

BMGV	240 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: butoxyacetic acid
------	---

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.

(Contd. on page 6)

## Safety data sheet

### According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 5)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· **Protection of hands:**

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.5$  mm

· **Penetration time of glove material**

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

· **Body protection:** Use protective suit. (EN-13034/6)

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Aerosol  
**Colour:** According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

**Melting point/Melting range:** Undetermined.

**Boiling point/Boiling range:** -44 °C

· **Flash point:** -97 °C

(Contd. on page 7)



## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 6)

· <b>Self-igniting:</b>	Product is not selfigniting.
· <b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· <b>Explosion limits:</b> <b>Lower:</b> <b>Upper:</b>	1.2 Vol % 12.0 Vol %
· <b>Vapour pressure at 20 °C:</b>	8300 hPa
· <b>Density at 20 °C:</b>	0.77 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.
· <b>Evaporation rate</b>	Not applicable.
· <b>Solubility in / Miscibility with water:</b>	Not miscible or difficult to mix.
· <b>Partition coefficient (n-octanol/water):</b>	Not determined.
· <b>Viscosity:</b> <b>Dynamic:</b> <b>Kinematic:</b>	Not determined. Not determined.
· <b>Solvent content:</b> <b>Organic solvents:</b>	100.0 %
· <b>9.2 Other information</b>	No further relevant information available.

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:****108-88-3 toluene**

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mus)

**78-93-3 butanone / MEK**

Oral	LD50	>2193 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit) 5000 mg/kg (rbt)

**67-63-0 propan-2-ol**

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50/6h	25000 mg/m <sup>3</sup> (rat)

(Contd. on page 8)



## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 7)

- **Primary irritant effect:**
- **Skin corrosion/irritation**  
Causes skin irritation.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity**  
Suspected of damaging the unborn child.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure**  
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard**  
May be fatal if swallowed and enters airways.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

###### 108-88-3 toluene

NOEC (7 day)	0.74 mg/l (Daphnia magna)
EC50/24h	84 mg/l (Activated Sludge)
EC50 (72h)	10 mg/l (algae)
LC50/96h	5.5 mg/l (Fish)
EC50/48h	3.78 mg/l (Daphnia magna)

###### 78-93-3 butanone / MEK

LC50/96h	2993 mg/l (Pimephales promelas)
EC50/48h	308 mg/l (Daphnia magna)

###### 67-63-0 propan-2-ol

LOEC (8 days)	1000 mg/l (algae)
LC50/96h	9640 mg/l (Pimephales promelas)
LC50 (24h)	9714 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

##### · Additional ecological information:

###### · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

###### · 12.5 Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 9)





## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016



**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 8)

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

- |   |   |
|---|---|
| · <b>14.1 UN-Number</b><br>· <b>ADR, ADN, IMDG, IATA</b>  | UN1950  |
| · <b>14.2 UN proper shipping name</b><br>· <b>ADR, ADN</b><br>· <b>IMDG</b><br>· <b>IATA</b>  | UN1950 AEROSOLS<br>AEROSOLS<br>AEROSOLS, flammable  |
| · <b>14.3 Transport hazard class(es)</b><br>· <b>ADR</b><br> |   |
| · <b>Class</b><br>· <b>Label</b>  | 2 5F Gases.<br>2.1  |
| · <b>ADN</b><br>· <b>ADN/R Class:</b>   | 2 5F  |
| · <b>IMDG, IATA</b><br>                                      |   |
| · <b>Class</b><br>· <b>Label</b>  | 2.1<br>2.1  |
| · <b>14.4 Packing group</b><br>· <b>ADR, IMDG, IATA</b>   | Void  |
| · <b>14.5 Environmental hazards:</b><br>· <b>Marine pollutant:</b>  | No  |
| · <b>14.6 Special precautions for user</b><br>· <b>Danger code (Kemler):</b><br>· <b>EMS Number:</b><br>· <b>Stowage Code</b>                   | Warning: Gases.<br>-<br>F-D,S-U<br>SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters. |

(Contd. on page 10)



## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 9)

· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 48
- National regulations:

Class	Share in %
NK	75-<100
- VOC-CH 100.00 %
- VOC-EU 766.0 g/l
- Danish MAL Code 5-3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.

(Contd. on page 11)



## Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 5

Revision: 24.10.2016

**Trade name: 20311 PM Xeramic® Carb & Choke Cleaner**

(Contd. of page 10)

- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.

- **Department issuing SDS:** Research & Development

- **Contact:** info@petromark.eu

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

- **\* Data compared to the previous version altered. \***

GB