

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **20319 PM Xeramic® Silicon Spray**

Article number: 20319

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

Product category PC24 Lubricants, greases, release products

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Lubricant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Petromark Automotive Chemicals

Rooswijkweg 316, 1951 ME Velsen-Noord, The Netherlands

www.petromark.eu info@petromark.eu Tel. +31 (0)251 211397

Further information obtainable from:

Petromark Automotive Chemicals: info@petromark.eu

1.4 Emergency telephone number:

Petromark Automotive Chemicals, Tel. +31 (0)251 211397

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02



GHS07



GHS09

Signal word Danger

(Contd. on page 2)



Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

Trade name: 20319 PM Xeramic® Silicon Spray

(Contd. of page 1)

· Hazard-determining components of labelling:

Pentane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P211 Do not spray on an open flame or other ignition source.

P280 Wear protective gloves / eye protection.

P271 Use only outdoors or in a well-ventilated area.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P403 Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****· 3.2 Mixtures****· Description:** Active substance with propellant**· Dangerous components:**

CAS: 109-66-0 EINECS: 203-692-4 Reg.nr.: 01-2119459286-30	Pentane Flam. Liq. 1, H224; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32	butane (containing < 0.1% butadiene (203-450-8)) Flam. Gas 1, H220; Press. Gas C, H280	25-<50%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1, H220; Press. Gas C, H280	10-<25%

· Additional information:**SECTION 4: First aid measures****· 4.1 Description of first aid measures****· After inhalation:** Supply fresh air; consult doctor in case of complaints.**· After skin contact:** Generally the product does not irritate the skin.**· After eye contact:** Rinse opened eye for several minutes under running water.**· After swallowing:** Do not induce vomiting; call for medical help immediately.**· 4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

(Contd. on page 3)



Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

Trade name: 20319 PM Xeramic® Silicon Spray

(Contd. of page 2)

- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
Water haze
Fire-extinguishing powder
Carbon dioxide
Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:**
Observe official regulations on storing packagings with pressurised containers.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.

(Contd. on page 4)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

Trade name: 20319 PM Xeramic® Silicon Spray

(Contd. of page 3)

 · **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

 · **Additional information about design of technical facilities:** No further data; see item 7.

· 8.1 Control parameters

 · **Ingredients with limit values that require monitoring at the workplace:**

109-66-0 Pentane

 WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane (containing < 0.1% butadiene (203-450-8))

 WEL Short-term value: 1810 mg/m³, 750 ppm
 Long-term value: 1450 mg/m³, 600 ppm
 Carc (if more than 0.1% of buta-1.3-diene)

74-98-6 propane

 OEL Short-term value: 3600 mg/m³, 2000 ppm
 Long-term value: 1800 mg/m³, 1000 ppm

· DNELs

109-66-0 Pentane

Oral	DNEL Long term-systemic	214 mg/kg bw/day (Consumer)
Dermal	DNEL Long term-systemic	214 mg/kg bw/day (Consumer)
		432 mg/kg bw/day (Worker)
Inhalative	DNEL Long term-systemic	643 mg/m ³ (Consumer)
		3000 mg/m ³ (Worker)

 · **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

 · **General protective and hygienic measures:** Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX/P2

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

· Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Wear gloves for the protection against chemicals according to EN 374



Protective gloves

Solvent resistant gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.5 mm

(Contd. on page 5)

Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

Trade name: 20319 PM Xeramic® Silicon Spray

(Contd. of page 4)

· Penetration time of glove material

For continuous contact we recommend gloves with breakthrough time of at least 240 minutes, with the preference given to a breakthrough time greater than 480 minutes. For short-term or splash guard we recommend the same. We are aware that suitable gloves that offer this level of protection may not be available. In that case, a shorter breakthrough time are acceptable as long as the procedures governing maintenance and timely replacement are followed. The thickness of the gloves is not a good measure of the resistance of the gloves against a chemical substance, because this depends on the exact composition of the material from which the gloves are made.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Use protective suit. (EN-13034/6)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties
· General Information
· Appearance:

Form:	Liquid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-44 °C

· Flash point: -97 °C

· Self-igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	1.4 Vol %
Upper:	10.9 Vol %

· Vapour pressure at 20 °C: 8300 hPa

· Density at 20 °C:	0.61 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.

· Solubility in / Miscibility with water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 6)



Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

Trade name: 20319 PM Xeramic® Silicon Spray

(Contd. of page 5)

- **Solvent content:**
 - **Organic solvents:** 90.0 %
- **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard**
May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

109-66-0 Pentane

NOEC (72h)	7.51 mg/l (Pseudokirchneriella subcapitata)
EC50 (72h)	10.7 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	4.26 mg/l (Oncorhynchus mykiss (96h))
EC50/48h	2.7 mg/l (Daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

(Contd. on page 7)



Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

Trade name: 20319 PM Xeramic® Silicon Spray






(Contd. of page 6)

- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**
· **ADR, ADN, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
· **ADR, ADN** UN1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS
· **IMDG** AEROSOLS (PENTANES), MARINE POLLUTANT
· **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
 
· **Class** 2 5F Gases.
· **Label** 2.1
- **ADN**
· **ADN/R Class:** 2 5F
- **IMDG**
 
· **Class** 2.1
· **Label** 2.1
- **IATA**

· **Class** 2.1
· **Label** 2.1
- **14.4 Packing group**
· **ADR, IMDG, IATA** Void

(Contd. on page 8)



Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

Trade name: 20319 PM Xeramic® Silicon Spray

(Contd. of page 7)

· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Pentane
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree) Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Gases.
· Danger code (Kemler):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· Transport category	2
· Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· National regulations:

Class	Share in %
NK	75-<100

· VOC-CH 90.00 %

· VOC-EU 545.4 g/l

· Danish MAL Code 2-1

(Contd. on page 9)



Safety data sheet

According to 1907/2006 EEC Article 31

Printing date: 24.10.2016

Version: 6

Revision: 24.10.2016

Trade name: 20319 PM Xeramic® Silicon Spray

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Research & Development

· **Contact:** info@petromark.eu

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark)

DNEL: Derived No-Effect Level (REACH)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 1: Flammable liquids – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· *** Data compared to the previous version altered. ***